

SUBMITTAL SHEET

69TANKTEE / FSBTANKTEE

Tank Tee

Attach an expansion tank to the water heater quicker and easier!

The 3/4 in. Tectite by Apollo Push To Connect x male Pipe Thread x Female Pipe Thread Expansion Tank Tee is the fastest and simplest way to install a thermal expansion tank to potable water piping systems connection to copper, CPVC, PE-RT and PEX pipe without the use of tools, solder, open flame or glue. The female threaded outlet is ideal for the installation of thermal expansion tanks. After applying the appropriate thread tape to the cold water male inlet on the top of the water heater, screw the Tank Tee into place until hand tight. Tighten slightly with pliers to ensure a leak free seal. Screw the expansion tank directly to the Tank Tee after applying thread tape. To finish the project simply insert the pipe into the push-to-connect to allow the high-strength stainless steel teeth to grip the pipe securely against the specially designed O-ring. Fitting removal and reuse is just as simple using a simple demount clip (sold separately). After assembly, fittings may be rotated for simpler installation in tight spaces. All Tectite by Apollo fittings are approved for use in both potable water and hydronic heating piping systems.

Features:

- Constructed of lead free dezincification resistant (DZR) brass for superior reliability and strength
- For use with 3/4 in. copper tube-sized pipe - CPVC, PE-RT, PEX, or Copper
- Fittings can be rotated after being installed for ease of use in tight spaces
- Ideal for potable water and hydronic heating applications
- Demount clip allows for fitting removal (sold separately)
- Corrosion resistant for greater longevity

Performance Rating:

- Maximum working pressure: 200 psi
- Maximum temperature: 250° F

Approvals:

- ASSE 1061/NSF 69
- IAPMO
- Meets UPC, IPC, cUPC standards

Approvals:

Attach Tank Tee to the water heater pipe nipple with pipe tape on male threads. Then, attach the expansion tank with pipe tape on male threads. Finally, attach Copper, CPVC, or PEX pipe to the push end – no tools needed!

Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	



Tank Tee								
Part Number	Description	H	W	D	Wt (lbs)	Carton Qty	UPC	
69TANKTEE	3/4 in. Push x 3/4 in. FIP x 3/4 in. FIP	2.11	7.00	1.00	0.75	5	670750361821	
FSBTANKTEE	3/4 in. Push x 3/4 in. FIP x 3/4 in. FIP	2.11	7.00	1.00	0.75	5	670750081729	