

PUSH TO CONNECT WATER HEATER CONNECTORS

SUBMITTAL SHEET

Water Heater Connectors

Tectite by Apollo Water Heater Connectors come in a variety of configurations and lengths. These connectors utilize push-to-connect technology and are removeable and reusable and can be installed in wet or dry locations. They can also be used with Copper, CPVC, PEX, or PE-RT pipe. For use with water in accessible locations only. Inspect every six months and replace if leaking or corroded.

Specifications:

- Braided Stainless Steel Water Heater Connectors
Max. Working Temperature: 250° F (121° C)
Max. Working Pressure: 200 psig (1379Kpa)
- Corrugated Stainless Steel Water Heater Connectors
Max. Working Temperature: 250° F (121° C)
Max. Working Pressure: 200 psig (1379Kpa)

Approvals:

- cUPC
- NSF/ANSI 61 & 372
- ASSE 1061

Installation:

On push-to-connect ends, first cut pipe. Mark insertion depth on pipe end using depth gauge (sold separately). Push and twist pipe onto connector end until end meets depth line. On female threaded ends, hand tighten plus 1/4 turn with wrench. DO NOT OVERTIGHTEN NUTS. Over tightening of nuts can cause product damage. Do not retighten the assembly after installation causing the flex to twist and kink. This product is to be inspected after installation and every 6 months thereafter. Replace if leaking, corroded, or damaged in any way. Do not connect to instant hot water heaters or install next to external heat sources. Replace product after 5 years.

Maintenance: Clean with water only. Keep flex dry and away from external heat or corrosive source. Do not expose to household cleaners or other corrosives. Inspect every 6 months. Replace immediately in the event of wear, corrosion, discoloration, visible damage, or leaks. Do not reuse this product if wear, corrosion, discoloration, visible damage, or leaks occurs.

| | |
|-----------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO Number: | |
| Representative: | |



PUSH -TO-CONNECT WATER HEATER CONNECTORS



Corrugated Stainless Steel Water Heater Connectors

| Part Number | Description | H | W | L | Wt (lbs) |
|--------------|-------------------------------------|------|------|-------|----------|
| FSBCSST34F18 | 3/4 in. CTS x 3/4 in. FNPT x 18 in. | 1.13 | 1.13 | 18.00 | 0.50 |
| FSBCSST34F24 | 3/4 in. CTS x 3/4 in. FNPT x 24 in. | 1.13 | 1.13 | 24.00 | 0.63 |



Braided Stainless Steel Water Heater Connectors

| Part Number | Description | H | W | L | Wt (lbs) |
|--------------|--|------|------|-------|----------|
| FSBBS34F12 | 3/4 in. CTS x 3/4 in. FNPT x 12 in. | 1.13 | 1.13 | 12.00 | 0.44 |
| FSBBS34F15 | 3/4 in. CTS x 3/4 in. FNPT x 15 in. | 1.13 | 1.13 | 15.00 | 0.48 |
| FSBBS34F18 | 3/4 in. CTS x 3/4 in. FNPT x 18 in. | 1.13 | 1.13 | 18.00 | 0.65 |
| FSBBS34F18BV | 3/4 in. CTS x 3/4 in. FNPT Ball Valve x 18 in. | 2.00 | 1.13 | 20.00 | 1.21 |
| FSBBS34F24 | 3/4 in. CTS x 3/4 in. FNPT x 24 in. | 1.13 | 1.13 | 24.00 | 0.71 |