

## SUBMITTAL SHEET

### PUSH TO CONNECT

# Electrical Fittings

Tectite Electrical is an industry-first range of UL-approved Push-To-Connect fittings for non-metallic flexible conduit. Installation is easy - simply push the fitting onto non-metallic flexible conduit. The result is a functionally superior and water-tight seal. It's non-metallic and this provides extra safety through assured grounding and the smooth interior walls make pulling wire easy, even around tight corners. The installation of type B non-metallic conduit to weatherproof outlet boxes, pool/spa equipment, central air conditioning units, and various other electrical enclosures or hubs just got tremendously easier with Tectite Electrical.

Tectite Electrical fittings are available in 1/2 in., 3/4 in., and 1 in. sizes in male adapter and male elbow configurations.

#### **Features:**

- Fast, clean and simple installation using push to connect technology
- Approved for direct burial
- Includes nut and integrated EPDM seal
- Requires no solvents or tools for installation or removal
- Removable and reusable
- Corrosion-proof for longevity

#### **Specifications & Approvals:**

- CSA
- UL

#### **Installation Instructions:**

Squarely cut the conduit to desired length. Mark the insertion depth using the depth gauge on the packaging. Insert conduit and twist into the fitting until the fitting edge meets the depth line. After assembly, fittings may be rotated for simpler installation in tight spaces.



# PUSH TO CONNECT

## Tectite Electrical Male Adapters

Part Number	Description	H	W	L	Wt (lbs)	Carton Qty	UPC
ELMA12	1/2 in. Non-Metallic Water Tight Push To Connect Straight Connector	2.25	1.50	1.50	0.04	15	850003465487
ELMA126JR	1/2 in. Non-Metallic Water Tight Push To Connect Straight Connector (6 Pack Jar)	2.25	1.50	1.50	0.04	8	850003465500
ELMA34	3/4 in. Non-Metallic Water Tight Push To Connect Straight Connector	2.50	1.75	1.75	0.07	10	850003465494
ELMA1	1 in. Non-Metallic Water Tight Push To Connect Straight Connector	2.75	2.00	2.00	0.10	10	850003465548

## Tectite Electrical Male Elbows

Part Number	Description	H	W	L	Wt (lbs)	Carton Qty	UPC
ELME12	1/2 in. Non-Metallic Water Tight Push To Connect Straight Connector	3.50	2.00	1.50	0.05	15	850003465517
ELME126JR	1/2 in. Non-Metallic Water Tight Push To Connect Straight Connector (6 Pack Jar)	3.50	2.00	1.50	0.05	8	850003465524
ELME34	3/4 in. Non-Metallic Water Tight Push To Connect Straight Connector	4.00	2.50	1.75	0.09	10	850003465531
ELME1	1 in. Non-Metallic Water Tight Push To Connect Straight Connector	4.75	2.83	2.00	0.13	10	850003465555